Serial No. 10/823,634

IN THE CLAIMS:

Please CANCEL claim 1, without prejudice or disclaimer.

Please ADD new claims as indicated below:

1-91. (CANCELED)

92. (NEW) An apparatus comprising:

a first compensator compensating wavelength dispersion, the first compensator having a constant wavelength dispersion characteristic over a plurality of wavelengths; and

a second compensator compensating wavelength dispersion after wavelength dispersion is compensated by the first compensator, wherein the first and second compensators together compensate for wavelength dispersion dependent on a respective wavelength of a transmission line.

- 93. (NEW) An apparatus as in claim 92, further comprising: a housing which houses, and thereby encloses, both the first and second compensators.
- 94. (NEW) An apparatus as in claim 92, further comprising: a substrate on which both the first and second compensators are fixed.
- 95. (NEW) An apparatus as in claim 92, further comprising: a substrate on which both the first and second compensators are fixed.
- 96. (NEW) An apparatus as in claim 92, wherein the respective wavelength is the wavelength of a respective signal light included in a wavelength division multiplexed (WDM) light transmitted through the transmission line and including a plurality of signal lights at different wavelength multiplexed together.
- 97. (NEW) An apparatus as in claim 92, wherein the first compensator is a virtually imaged phased array (VIPA) dispersion compensator.
 - 98. (NEW) An apparatus comprising: first means for compensating wavelength dispersion, the first means having a constant

wavelength dispersion characteristic over a plurality of wavelengths; and

second means for compensating wavelength dispersion after wavelength dispersion is compensated by the first means, wherein the first and second means together compensate for wavelength dispersion dependent on a respective wavelength of a transmission line.

- 99. (NEW) An apparatus as in claim 98, further comprising: a housing which houses, and thereby encloses, both the first and second compensators.
- 100. (NEW) An apparatus comprising:

a first compensator compensating for wavelength dispersion, the first compensator having a constant wavelength dispersion characteristic over a plurality of wavelengths; and a second compensator compensating for dispersion slope over the plurality of wavelengths after the compensation by the first compensator.

- 101. (NEW) An apparatus as in claim 100, further comprising: a housing which houses, and thereby encloses, both the first and second compensators.
- 102. (NEW) An apparatus as in claim 100, further comprising: a substrate on which both the first and second compensators are fixed.
- 103. (NEW) An apparatus as in claim 101, further comprising: a substrate on which both the first and second compensators are fixed.
- 104. (NEW) An apparatus as in claim 100, wherein the first and second compensators together compensate for dispersion of a respective wavelength of a respective signal light included in a wavelength division multiplexed (WDM) light transmitted through a transmission line and including a plurality of signal lights at different wavelength multiplexed together.
- 105. (NEW) An apparatus as in claim 100, wherein the first compensator is a virtually imaged phased array (VIPA) dispersion compensator.